

磁性液位开关 Magnetic Level Switches

PP材质垂直安装型

Vertical Type (PP)



LS04
M10 × L:100



LS05
M10 × L:75

PP材质水平侧装型

Horizontal Type (PP)



LS06
M12 × L:54



LS07
M16 × L:83



LS14
1/2"NPT L:80

特点及用途 Advantages and Applications

- ◆ 经典设计，尺寸紧凑；
Classic design, compact size;
- ◆ 常开，常闭可选择；
Choice of normal open or normal close;
- ◆ 无待机功率消耗；
No standby power requirement;
- ◆ 客户可自定义动作距离，线长和端子；
Customer can define activated distance, cable length and connector;
- ◆ 密封设计，可工作于恶劣环境，性能稳定，寿命超长；
Hermetically sealed, suit to tough environment and long life;
- ◆ 在家电、汽车和工业控制等领域大量使用。
Widely used in household appliances, automotive applications and control technology.

型号 Type	LS04	LS05	LS06	LS07	LS14
特点 Features	可设计双浮球 2 floats on one shaft	可设计双浮球 2 floats on one shaft	自内安装 Mounting form inside	自内安装 Mounting form inside	自外安装，无需密封 Mounting form outside, No sealing necessary
触点形式 Contact Form	2A,2B	2A,2B	1A,1B	1A,1B	1A,1B
触点负载 Contact Rating Max	10/50W	10/50W	10/50W	10/50W	10/50W
最大开关电压 Max. Switching Voltage	200/300	200/300	200/300	200/300	200/300
最小击穿电压 Min. Breakdown Voltage	250/500	250/500	250/500	250/500	250/500
最大开关电流 Max.Switching Current	0.5A	0.5A	0.5A	0.5A	0.5A
最大负载电流 Max.Carry Current	1.0/2.5	1.0/2.5	1.0/2.5	1.0/2.5	1.0/2.5
工作温度范围 Operation Temperature	-20℃ to +80℃				
外壳材料 Housing Material	PP				

订货信息 Order Information

SERIES	CONTACT FORM	SWITCH MODEL	CABLE LENGTH(mm)	TERMINATION
LS**-	XX	X	X	W
OPTIONS	1A: 1 Form A 1B: 1 Form B	1: 10w	1: 100mm	W: 5mm of wire stripped and tinned
		2: low High Voltage	2: 300mm	
		3: 50W High Voltage	3: 500mm	